

ILS or LOC RWY 23

LOC I-POB 110.9	APCH CRS 228°	Rwy Idg TDZE Arprt Elev 7501 200 218	AL-147 [USAF]	POPE AAF (KPOB)
---------------------------	-------------------------	--	---------------	-----------------

RADAR required

- * When ALS inop, increase RVR to 40 and vis to ¾ mile.
- ** When ALS inop, increase CAT AB RVR to 55 and vis to 1 mile; CAT CD RVR to 60, vis to 1½ miles.
- *** Circling not authorized SE of Rwy 5-23.
- **** When ALS inop, increase CAT AB RVR to 55 and vis to 1 mile; CAT CD vis to 1½ miles.

ATIS
132.3 353.725

FAYETTEVILLE APP CON
125.175 285.575 (271° - 090°)
133.0 290.25 (091° - 270°)

TOWER
135.025 291.1

GND CON
124.55 275.8

CLNC DEL
124.55 275.8

MISSED APPROACH: Climbing right turn to 2000 direct AWGUS and hold.
For acft not equipped with TACAN or suitable RNAV system with GPS: Climbing right turn to 2000 hdg 350°, expect RADAR vectors.

CAUTION: Avoid R-5311 A, B, C located 2.5 DME West of field

POPE Chan 85 POB

LOCALIZER 110.9 I-POB

SIMMONS AAF

EMERG SAFE ALT 100 NM 5300 FROM "POB" TACAN

ELEV	218	TDZE	200
Rwy 5 Idg 7501'			
Rwy 23 Idg 7501'			

TACAN

WIBAX 1.6

KECCN 3.7

NAYIN 4.8 RADAR

ACENO 12

GS 3.00° TCH 54

CATEGORY	A	B	C	D
S-LS 23*	400/24		200	(200-½)
S-LOC 23**	620/24	420 (500-½)	620/40	420 (500-¾)
*** C CIRCLING	760-1	542 (600-1)	920-2 702 (800-2)	1060-2½ 842 (900-2¾)
WITHOUT LAST STEPDOWN FIX				
S-LOC 23****	640/24	440 (500-½)	640/45	440 (500-¾)

HIRL Rwy 5-23
LIRL Rwy 050°-230°
REIL Rwy 5

FAF to MAP 3.2 NM

Knots	60	90	120	150	180
Min:Sec	3:12	2:08	1:36	1:17	1:01

SE-2, 16 MAY 2024 to 13 JUN 2024

SE-2, 16 MAY 2024 to 13 JUN 2024