


WAAS CH 49034 W17A	APP CRS 171°	Rwy Idg TDZE 782 Apt Elev 782
--	------------------------	---


RNAV (GPS) RWY 17
ANDERSON RGNL (AND)

▼ DME/DME RNP-0.3 NA. When local altimeter setting not received, use Clemson altimeter setting and increase all MDA 60 feet and increase LP, LNAV and Circling Cts C/D visibility ¼ mile. ▲ Straight-in Rwy 17 NA at night, Circling Rwy 17, 35 NA at night. 17, 35 helicopter visibility reduction below 1 SM NA.	MISSED APPROACH: Climb to 2500 direct ZAROM and hold.
--	---

ASOS 120.675	GREER APP CON ★ 118.8 270.275	CTAF 123.60
------------------------	---	-----------------------



4 NM Holding Pattern UTOTE				
3200 ← 351° 171° → 2500				
WUVTO TUKUC 1.8 NM to RWY 17 3.00° TCH 45 1400				
6.9 NM 3.5 NM 1.8 NM				
CATEGORY	A	B	C	D
LP MDA	1200-1	418 (500-1)	1200-1½	418 (500-1½)
LNAV MDA	1220-1	438 (500-1)	1220-1¼	438 (500-1¼)
CIRCLING	1260-1 478 (500-1)	1320-1 538 (600-1)	1440-1¾ 658 (700-1¾)	1500-2¼ 718 (800-2¼)



SE-2, 16 MAY 2024 to 13 JUN 2024

SE-2, 16 MAY 2024 to 13 JUN 2024