

LOC/DME I-JNX
111.15
Chan **48** (Y)

APP CRS
032°

Rwy Idg **5500**
TDZE **147**
Apt Elev **164**

ILS Y or LOC Y RWY 3
JOHNSTON RGNL (JNX)

GPS required. VDP NA with Erwin altimeter setting. When local altimeter setting not received, use Erwin altimeter setting: increase DA to 447 feet, increase all MDA 60 feet and S-LOC 3 Cat C/D and Circling Cat A visibility ¼ mile, and JONIR fix minimums S-LOC 3 Cat C/D visibility ⅓ mile and Circling Cat C ¼ mile. For inop MALSR, increase S-LOC 3 Cat C/D visibility to 2½ mile and JONIR fix minimums S-LOC 3 Cat C/D to 1¾ mile. For inop MALSR when using Erwin altimeter setting, increase S-ILS all Cats visibility to 1 mile.

MALSR

MISSED APPROACH: Climb to 3400 direct JNALL and hold, continue climb-in-hold to 3400.

AWOS-3 120.225	RALEIGH APP CON 125.3 353.675	GCO 135.075	UNICOM 122.725 (CTAF) 0
--------------------------	---	-----------------------	--

MISSED APCH FIX

212°

032°

4 NM

JNALL

736

430

238

613

605

JONIR I-JNX **3.5**

JHDI I-JNX **5.3** RADAR

1500

032°

212°

4 NM

(IF/IAF) WITIX I-JNX **12.3**

SEYMOUR JOHNSON ECHO MOA

LOCALIZER 111.15
I-JNX
Chan 48 (Y)

30 NM to WITIX

30 NM to WITIX

30 NM to WITIX (NoPT)

3400

3000

4000

122°

122°

302°

302°

1148

GPS REQUIRED

4 NM Holding Pattern

WITIX I-JNX **12.3**

3000

212°

032°

032°

GS 3.00° TCH 45

1500

7 NM

1.8 NM

0.5

1.8 NM

JHDI I-JNX **5.3** RADAR

JONIR I-JNX **3.5**

*I-JNX **3.0**

I-JNX **1.2**

3400

JNALL

*LOC only.

CATEGORY	A	B	C	D
S-ILS 3		397-½	250 (300-½)	
S-LOC 3	940-½ 793 (800-½)	940-¾ 793 (800-¾)	940-1¾	793 (800-1¾)
CIRCLING	940-1 776 (800-1)	940-1¼ 776 (800-1¼)	940-2½ 776 (800-2½)	1100-3 936 (1000-3)
JONIR FIX MINIMUMS				
S-LOC 3	780-½	633 (700-½)	780-1⅔	633 (700-1⅔)
CIRCLING	780-1	616 (700-1)	920-2¼ 756 (800-2¼)	1100-3 936 (1000-3)

032° 4.1 NM from FAF

MIRL Rwy 3-21 **0**

REIL Rwy 21 **0**

SMITHFIELD, NORTH CAROLINA
Amdt 1A 18AUG16

35°32'N-78°23'W

JOHNSTON RGNL (JNX)
ILS Y or LOC Y RWY 3