

LOC I-MEI <u>110.1</u>	APP CRS 011°	Rwy Idg 9013 TDZE 289 Apt Elev 298
----------------------------------	------------------------	---

ILS or LOC RWY 1
KEY FLD (MEI)

RNAV 1- GPS or DME required for procedure entry.

V Circling NA southeast of Rwy's 1 and 22. When local altimeter not received, use Hattiesburg/Laurel Rgnl altimeter setting and increase all DA 138 feet and all MDA 140 feet. **A** S-LS 1 all Cats visibility to RVR 3500, S-LOC 1 Cat B visibility to RVR 4000, Cat C, D, and E visibility 3/8 mile, and Circling Cats B and D visibility 1/4 mile, Cat C visibility 1/2 mile; increase ZUOFG Fix minimums S-LOC 1 Cats C, D, and E to RVR 6000, and Circling Cat C visibility 1/2 mile, Cat D and E visibility 1/4 mile. For inop MALSR when using Hattiesburg/Laurel Rgnl altimeter setting, increase S-LS 1 all Cats visibility to RVR 6000 and S-LOC 1 Cat E visibility to 1 3/8 mile; increase ZUOFG Fix minimums S-LOC 1 Cat E visibility to 2 miles. Circling Rwy 22 NA at night. **RVR 1800 authorized with use of FD or AP or HUD to DA (NA when using Hattiesburg/Laurel Rgnl altimeter setting).

MALSr

A5

MISSED APPROACH:
Climb to 1100 then
climbing left turn
to 3000 on MEI
VORTAC R-216 to
PAULD INT/MEI 13.3
DME and hold.

ATIS	MERIDIAN APP CON ★	KEY TOWER ★	GND CON	CLNC DEL	UNICOM
126.475 291.675	120.5 269.325	133.975 (CTAF) 0 257.8	121.9 348.6	121.9 348.6	122.95

