

APP CRS
344°

Rwy Idg
TDZE
2724

Apt Elev
2724

RNAV (GPS) RWY 34

ROSEBUD SIOUX TRIBAL (STUO)

RNP APCH - GPS.


▼

NA

Rwy 34 helicopter visibility reduction below 1 SM NA. Use Valentine altimeter setting, when not received, use Martin altimeter setting and increase all MDAs 100 feet and LNAV visibility Cat B ¼ SM, Cat C ½ SM, and Circling visibility Cat B ¼ SM, Cat C ½ SM. Procedure NA at night.

MISSED APPROACH: Climb to 3400 then climbing right turn to 5000 direct GLUGS and hold.

AWOS-3P 119,075	VTN ASOS 118,075	DENVER CENTER 127.95 338.2	CTAF 122.9 0
--------------------	---------------------	-------------------------------	-----------------



ELEV 2724

D

TDZE 2724

91

0.9% UP

4801 X 75

34

344°

MIRL Rwy 16-34 0

3400	5000	GLUGS	VGSI and descent angles not coincident (VGSI Angle 3.00/TCH 30).	GLUGS	5 NM Holding Pattern
RW34 3.00° TCH 40 4200 344° 164° 6000 5000					
4.5 NM 6 NM					
CATEGORY	A	B	C	D	
LNAV MDA	3380-1	656 (700-1)	3380-1 7/8 656 (700-1 7/8)	NA	
CIRCLING	3380-1	656 (700-1)	3440-2 716 (800-2)	NA	

NC-1, 16 MAY 2024 to 13 JUN 2024

NC-1, 16 MAY 2024 to 13 JUN 2024